



Samonasávací odstředivá čerpadla

Výběr čerpadel pro 2-pólové elektrické motory

		3450 RPM 60 Hz	2900 RPM 50 Hz																
H m		50				7	7	7	7	7	10								
		57	40				5	5	5	5	5	7	10	10	10				
		45	31,5				4	5	5	5	5	5	5	10	10	10			
		36	25	2	2	2	2	4	4	4	4	5	5	5	9	8	10		
		29	20	2	2	2	2	4	4	4	4	4	4	5	9	9	8	8	
		23	16	1	1	2	3	3	2	4	4	4	4	6	9	9	9	8	
		18	12,5	1	1	1	1	1	1	3	3	4	4	6	6	9	9	8	8
		14	10	1	1	1	1	1	1	3	3	3	3	6	6	6	9	8	8
		11,5	8	1	1	1	1	1	1	1	3	3	3	6	6	6	9	8	8
		9	6,3	1	1	1	1	1	1	1	3	3	3	6	6	6	9	8	8
		7,2	5	1	1	1	1	1	1	1	3	3	3	6	6	6	9	8	8
				5	6,3	8	10	12,5	16	20	25	31,5	40	50	63	80	100	125	50 Hz
			6	7,6	9,6	12	15	19,2	24	30	38	48	60	76	96	120	150	60 Hz	
			Q m³/h																

1	2	3	4	5	6	7	8	9	10
S 40	S 45	S 50	S 60	S 63	S 80	S 68	S 100	S 83	S 88

